

## Technical Datasheet

# PRIMER-CLASSIC

## Acrylic, micronized, water-based primer

### Description

PRIMER-CLASSIC is an acrylic, micronized, water-based primer featuring strong adhesion and high penetrating ability. Ideal for use in indoor spaces as it is odorless, and environment- and user- friendly. Its blue color makes it easily visible in fully primed surfaces.

### Fields of application

Suitable for use on new surfaces, including plaster, concrete, brick, etc., to be covered with emulsion paints. Can also consolidate and protect from moisture porous surfaces covered with lime, adhesives, or old paints.

### Technical data

Form:	emulsion
Color:	transparent blue
Volume solids:	18 ± 1 %
Density: (EN ISO 2811-1)	1.00 kg/l
pH: (EN ISO 4316)	8-9
Drying time: (EN ISO 9117)	1 h (touch day)
Recoat time:	4 h

Cleaning of tools:  
Remove as much paint as possible from the used tools before cleaning. Clean the tools thoroughly with water and detergent immediately after use.

### Directions for use

#### 1. Substrate

The surface to be primed must be dry and free of dust, grease, dirt etc. while any imperfections on plaster should be restored.

#### 2. Application

PRIMER-CLASSIC is applied in one coat thinned up to 50% with clean water. For highly porous substrates, use it undiluted. It is applied by brush, roller, or spray.

### Coverage

10-15 m<sup>2</sup>/l per coat, depending on surface absorbency and thinning percentage.

### Packaging

PRIMER-CLASSIC is available in 1 l, 5 l and 10 l plastic containers.

### Shelf life – Storage

24 months from production date if stored in original, unopened packaging, in temperature between +5°C and +35°C. Protect from direct sunlight and frost.

### Remarks

Temperature during application should range between +10°C and +35°C.

### Volatile organic compounds (VOCs)

According to Directive 2004/42/CE (Annex II, table A), the maximum allowed VOC content for the product subcategory h, type WB, is 30g/l (2010) for the ready-to-use product.

The ready-to-use product PRIMER-CLASSIC contains max. 30 g/l VOC.

#### ISOMAT S.A.

BUILDING CHEMICALS AND MORTARS

#### MAIN OFFICES - FACTORY:

17th km Thessaloniki - Ag. Athanasios Road,  
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,  
Tel.: +30 2310 576 000, Fax: +30 2310 576 029

[www.isomat.eu](http://www.isomat.eu) e-mail: [support@isomat.eu](mailto:support@isomat.eu)